



## ŠKATUĽOVÉ ROZVODKY IP 67

y=2 (sivá), 5 (čierna)

Vyhovuje  
STN EN 60670-1  
STN EN 60670-22

IP 67/400 V

**PA**

**A1÷E**

**F**

$I_{max} \leq 16 A$



**A1**


**B÷F**

$I_{max} > 16 A$


bez podložky    nutná podložka



6455-11P/y



6455-11P (12P)



6455-26P (27P)



6455-26P/y

Utesňovací rozsah pre 6455-11P (12P) 8 až 16 mm.

Utesňovací rozsah pre 6455-26P (27P) 9 až 13 mm, 15 až 19 mm.



6455-12P/y

Typ	Príslušenstvo v balení	Prierez (mm <sup>2</sup> )	Mostíky/Svorky L N PE	Objednávacie číslo	Balenie (ks)
6455-11P/2	vývodka	4	3/4 1/4 1/4	10002855.00	50
6455-11P/5	4 x Pg 16			10002857.00	
6455-12P/2	vývodka	4	3/4 1/4 -	10002856.00	50
6455-12P/5	4 x Pg 16			10002858.00	
6455-26P/2	vývodka	6	3/4 1/4 -	10003166.00	20
6455-26P/5	4 x Pg 21			10003170.00	
6455-27P/2	vývodka	6	3/4 1/4 1/4	10003167.00	20
6455-27P/5	4 x Pg 21			10003171.00	

Poznámka: 6455-2xP/y je na 660 V



6455-27P/y

## ŠKATUĽOVÉ ROZVODKY IP 54



6455-30

Vyhovuje  
STN EN 60670-1  
STN EN 60670-22

IP 54/400 V

**PP**

**A1÷E**

**F**

$I_{max} \leq 16 A$





**A1**

**B÷F**

$I_{max} > 16 A$

bez podložky    nutná podložka



Utesňovací rozsah pre 6455-30,(31,32) 4 až 17 mm.



6455-31

Typ	Príslušenstvo v balení	Prierez (mm <sup>2</sup> )	Mostíky/Svorky L N PE	Objednávacie číslo	Balenie (ks)
6455-30		-	- - -	10006512.00	20
6455-31	4 x Pg 13,5	4	3/4 1/4 1/4	10006513.00	20
6455-32		4	3/4 1/4 -	10006724.00	20



6455-32