


CORRUGATED PIPE PVC TYPE LIGHT 320N**UV RESISTANT**

 NORM PN-EN 61386-1 PN-EN 61386-22

Material: Self-extinguishable PVC (Calcium -Zinc stabilization)
/ Pipes with tensile steel wire \varnothing 0,5m m inside




Dimension [A] / [B] :	Corrugated pipe PVC, type light 320N, light gray color			
	Without pilot		With pilot	
	Catalogue No.	 #	Catalogue No.	 #
16 / 11	6109-25P	25 m	6160-25P	25 m
16 / 11	6109-50P	50 m	6160-50P	50 m
20 / 14,5	6100A-25P	25 m	6161A-25P	25 m
20 / 14,5	6100A-50P	50 m	6161A-50P	50 m
25 / 19	6102A-25P	25 m	6163A-25P	25 m
25 / 19	6102A-50P	50 m	6163A-50P	50 m
32 / 25	6110P	25 m	6166-25P	25 m
32 / 25	6110-50P	50 m	6166-50P	50 m
40 / 33	6167-25	25 m	6168-25	25 m

**CORRUGATED PIPE PVC TYPE 750N****UV RESISTANT**

 NORM PN-EN 61386-1:2011/A1:2019-08, PN-EN 61386-22:2005/A11:2011

Material: Self-extinguishable PVC (Calcium -Zinc stabilization)
/ Pipes with tensile steel wire \varnothing 0,5m m inside



Corrugated pipe PVC Dimension [A] / [B] :	Corrugated pipe PVC type 750N		Corrugated pipe PVC type 750N with pilot	
	Catalogue No.	 #	Catalogue No.	 #
	16 / 11	6109-25/750P	25 m	6160-25/750P
16 / 11	6109-50/750P	50 m	6160-50/750P	50 m
20 / 14,5	6100A-25/750P	25 m	6161A-25/750P	25 m
20 / 14,5	6100A-50/750P	50 m	6161A-50/750P	50 m
25 / 19	6102A-25/750P	25 m	6163A-25/750P	25 m
25 / 19	6102A-50/750P	50 m	6163A-50/750P	50 m
32 / 25	6110/750P	25 m	6166-25/750P	25 m
32 / 25	6110-50/750P	50 m	6166-50/750P	50 m
40 / 33	6167-25/750	25 m	6168-25/750	25 m




CAR TYPE CORRUGATED PIPE - SIMPLE AND DISSECTED

 NORM PN-EN 61386-1 PN-EN 61386-22

Car type corrugated pipe is used for protection of cables against moisture and mechanical damage. In industry, it helps to protect electronic equipment, controllers, electrotechnical devices.

Black color. Material: LDPE




Dimension [A] mm / [B] mm:	Catalogue number - plain	Catalogue number - dissected	 #
10 / 7	G.6157P	G.6157RP	100 m
12 / 9	G.6158P	G.6158RP	100 m
16 / 11	G.6150P	G.6150RP	100 m
18 / 13,5	G.6151P	G.6151RP	100 m
20 / 14,5	G.6152P	G.6152RP	100 m
25 / 19	G.6153P	G.6153RP	50 m
32 / 25	G.6155P	G.6155RP	50 m



FLEXIBLE SPIRAL CORRUGATED PIPES 320 N, SELF- EXTINGUISHABLE, UV RESIST

 NORM EN 61386-1, EN 61386-23



Type: light 320N

Working temperature: -5 to 60 °C


Impact resistance: IK07

Non-spreading flame: self-extinguishing VO

Insulation Resistance > 100 Mega Ohm



Dielectric strength: 2000V 50Hz

Cat. No.	Dimensions A/B	Color	📦#
17008C	12,4 / 8	●	30 m
17010C	14,6 / 10		
17012C	16,2 / 12		
17016C	20,2 / 16		
17020C	24,2 / 20		
17025C	29,6 / 25		
17032C	37,2 / 32		
17040C	45,3 / 40		
17050C	56 / 50		
17012	16,2 / 12		
17016	20,2 / 16		
17020	24,2 / 20		
17025	29,6 / 25		



CABLE DUCTS

 NORM PN-EN 50085-2-1



Dimension AxB	Catalogue Numbers - colors:				 # white	 # color
	white 	black 	light brown 	dark brown 		
15x10	K.1510	K.1510C	K.1510JBR	K.1510CBR	80 mb / 40 pcs	80 mb / 40 pcs
17x15	K.1715	K.1715C	K.1715JBR	K.1715CBR	42 mb / 21 pcs	42 mb / 21 pcs
20x18	K.2018	K.2018C	K.2018JBR	K.2018CBR	60 mb / 30 pcs	60 mb / 30 pcs
25x15	K.2515	K.2515C	K.2515JBR	K.2515CBR	60 mb / 30 pcs	60 mb / 30 pcs
32x15	K.3215	K.3215C	K.3215JBR	K.3215CBR	48 mb / 24 pcs	48 mb / 24 pcs
32x30	K.3230	K.3230C	K.3230JBR	K.3230CBR	56 mb / 28 pcs	56 mb / 28 pcs
40x25	K.4025	K.4025C	K.4025JBR	K.4025CBR	50mb / 25 pcs	50mb / 25 pcs
40x40	K.4040	-	K.4040JBR	K.4040CBR	48 mb / 24 pcs	48 mb / 24 pcs
50x18	K.5018	-	-	-	60 mb / 30 pcs	-
60x40	K.6040*	-	-	-	32 mb / 16 pcs	-
90x60	K.9060*	-	-	-	12 mb / 6 pcs	-
110x60	K.11060*	-	-	-	8 mb / 4 pcs	-
130x60	K.13060*	-	-	-	8 mb / 4 pcs	-

A. Mounting boxes

B. Power equipment, cable extenders

C. Housing, distribution boards

CZ. Pipes, ducts

D. Lighting equipment

E. Terminal strips

H. Cable clips and ties

R. Lightning installation